



Subject to technical alterations

Portable separator, Guide Curb

THE ORIGINAL



- The single separator units are connected with a very solid moulded-in metal hook.
- The stable, but flexible connection guarantees enough clearance in order to set up different curves (90°-angle to about 11 x 11m).
- The manifold anti-slide system on the bottom of each unit ensures an excellent laying stability on the road surface. It can be easily exchanged after abrasion.
- The horizont klemmfix separator does not have to be glued or screwed to the road.
- In the contrary to road studs or road marking tapes, no residuals of glue are left on the lane. This avoids the danger of so-called phantom markings.
- Built-in one-size-fits-all slot accepts all delineators, type Leitboy.
- Lateral climbing edges allow vehicles firstly to climb on- and secondly to press down the separator whilst driving over. This aids position stability to the separator.
- The reflective arch with 14 cats' eyes reflectors, depict the raised profile. This helps in particular motorcyclists to notice an elevation on the lane, especially at night.

Portable separator, Guide Curb



Separator, Guide Curb, LN60

- Original Klemmfix Hook & Bolt system
- Lateral climbing edges
- Moderate weight, easy installation
- Made of heavy duty 100% recycled composite.
- A 90° -curve can be laid out on approx. 11 x 11m
- Units can, but must NOT, be bolted together (Art.-no.: 766209 or 766202, page 64)
- Snap-in reflective arches may be installed, for additional nighttime visibility

Part No.	Pack Qty.
25581	50
25581weiss	50

Dimensions (LxWxH): 1,000 x 270 x 90 mm
Weight: approx. 16.0 kg

Certified by the BAST acc. to
 TL Leitelemente/No. 94 5 S 001/LU



End piece A, LN61

- One side slanted down
- Other side with solid metal hook
- Anti-slide system
- Made of heavy duty 100% recycled composite

Part No.	Pack Qty.
<i>end piece A</i>	
25582	1
25582weiss	1
<i>end piece B</i>	
25583	1
25583weiss	1

End piece B, LN62

- One side slanted down
- Other side with slot for connecting hook
- Anti-slide system
- Made of heavy duty 100% recycled composite

end piece A
Dimensions (LxWxH): 440 x 270 mm
Weight: approx. 5.6 kg

end piece B
Dimensions (LxWxH): 480 x 270 mm
Weight: approx. 5.3 kg

Certified by the BAST acc. to
 TL Leitelemente/No. 94 5 S 001/LU



Reflective arch L65

- 14 cats's eyes
- Snap-in fixation
- Rides exactly on separator's profile
- Break proof plastic
- Application of reflective arches is optional however, strongly recommended on motorways and in work zones, especially on nighttime.

Part No.	Pack Qty.
25584	50
25584weiss	50

Dimensions (LxWxH): 180 x 56 x 60 mm
Weight: approx. 0.2 kg

Certified by BAST/Cert.-no. 3194



Subject to technical alterations